

PRODUCT SPECIFICATIONS

NEMA STANDARD EFFICIENCY SINGLE PHASE CAST IRON								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
CSPHK-142	230	39	7.5	1.15	8.63	NSF ²	6" x 4"	270
CSPHL-143	230	46	10	1.15	11.50	NSF ²	6" x 4"	275
NEMA STANDARD EFFICIENCY SINGLE PHASE EPOXY COATED CAST IRON								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
CCSPHK-142	230	39	7.5	1.15	8.63	NSF ²	6" x 4"	270
CCSPHL-143	230	46	10	1.15	11.50	NSF ²	6" x 4"	275
NEMA STANDARD EFFICIENCY THREE PHASE CAST IRON								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
CSPHK3-142	208-230/460	21.2-19.2/9.6	7.5	1.25	9.38	NSF ²	6" x 4"	265
CSPHL3-143	208-230/460	27.6-24.4/12.2	10	1.25	12.50	NSF ²	6" x 4"	270
CSPHM3-144	208-230/460	44.2-40/20	15	1.25	18.75	NSF ²	6" x 4"	280
CSPHN3-145	208-230/460	55.3-50/25	20	1.25	25.00	NSF ²	6" x 4"	325
NEMA STANDARD EFFICIENCY THREE PHASE CAST IRON - 200V								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
CSPH2K3-142	200	22.1	1.15	1.25	9.38	NSF ²	6" x 4"	265
CSPH2L3-143	200	28.1	1.25	1.25	12.50	NSF ²	6" x 4"	270
CSPH2M3-144	200	42.3	1.25	1.25	18.75	NSF ²	6" x 4"	280
CSPH2N3-145	200	57.3	1.25	1.25	25.00	NSF ²	6" x 4"	350
NEMA STANDARD EFFICIENCY THREE PHASE EPOXY COATED CAST IRON								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
CCSPHK3-142	208-230/460	21.2-19.2/9.6	7.5	1.25	9.38	NSF ²	6" x 4"	265
CCSPHL3-143	208-230/460	27.6-24.4/12.2	10	1.25	12.50	NSF ²	6" x 4"	270
CCSPHM3-144	208-230/460	44.2-40/20	15	1.25	18.75	NSF ²	6" x 4"	280
CCSPHN3-145	208-230/460	55.3-50/25	20	1.25	25.00	NSF ²	6" x 4"	325
NEMA STANDARD EFFICIENCY THREE PHASE EPOXY COATED CAST IRON - 200V								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
CCSPH2K3-142	200	22.1	7.5	1.15	8.63	NSF ²	6" x 4"	265
CCSPH2L3-143	200	28.1	10	1.25	12.50	NSF ²	6" x 4"	270
CCSPH2M3-144	200	42.3	15	1.25	18.75	NSF ²	6" x 4"	280
CCSPH2N3-145	200	57.3	20	1.25	25.00	NSF ²	6" x 4"	350
SINGLE PHASE CAST IRON WITHOUT STRAINER - 50 HZ								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
5CSPHJ-142	220-240	35.5-32.5	5	1.00	5		6" x 4"	270
5CSPHK-143	220-240	43.0-39.4	7.5	1.00	7.5		6" x 4"	280
THREE PHASE CAST IRON WITHOUT STRAINER - 50 HZ								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs)
5CSPHJ3-142	220-240/380-415	13.0/6.9	5	1.00	5		6" x 4"	260
5CSPHK3-143	220-240/380-415	20.7-21.5/12.0/12.4	7.5	1.00	7.5		6" x 4"	270
5CSPHL3-144	220-240/380-415	27.0-27.5/15.6-15.9	10	1.00	10		6" x 4"	280
5CSPHM3-145	220-240/380-415	38.9-20.6	15	1.00	15		6" x 4"	300
THREE PHASE EPOXY COATED CAST IRON WITHOUT STRAINER - 50 HZ								
Product	Voltage	AMPS ¹	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (ANSI Flange)	Carton Wt (Lbs.)
5CCSPHJ3-142	220-240/380-415	13.0/6.9	5	1.00	5		6" x 4"	260
5CCSPHK3-143	220-240/380-415	20.7-11.0	75	1.00	7.5		6" x 4"	270
5CCSPHL3-144	220-240/380-415	26.9-14.3	10	1.00	10		6" x 4"	280
5CCSPHM3-145	220-240/380-415	38.9-20.6	15	1.00	15		6" x 4"	300

1: Amp draw may vary depending on motor manufacturer.
2: 'NSF(1)' indicates that pump bears a NSF mark signifying evaluation to NSF Standard 50 for Self-Priming Centrifugal Pumps for Swimming Pools and Spas.
3: 'NSF(2)' indicates that product bears a NSF mark signifying evaluation to NSF Standard 50 for Materials and Components.
4: Product may have been evaluated to other state and local regulatory standards. Listing status may change. Always confirm status with appropriate agency if in doubt.
5: Thermoplastic PVC socket style.