

ENERGY EFFICIENT SINGLE SPEED WITH STRAINER

Product	Model	Voltage	Full Load Amps	Primary Listings and Certifications ²	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
340350	AFP-75	115/230	9.6/4.8	UL ¹	2" x 2"	40	A
340351	AFP-120	115/230	9.6/4.8	UL ¹	2" x 2"	40	B
340352	AFP-150	115/230	12.0/6.0	UL ¹	2" x 2"	43	D
340353	AFP-180	115/230	12.0/6.0	UL ¹	2" x 2"	46	E

ENERGY EFFICIENT SINGLE SPEED WITHOUT STRAINER

Product	Model	Voltage	Full Load Amps	Primary Listings and Certifications ²	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
340300	AF-75 ³	115/230	9.6/4.8	UL ¹	2" X 2"	37	A
340301	AF-120 ³	115/230	9.6/4.8	UL ¹	2" X 2"	37	C
340302	AF-180 ³	115/230	12.0/6.0	UL ¹	2" X 2"	40	F

1: 'UL' indicates that pump bears a specific UL mark signifying evaluation to U.S. Standards UL1081 for Permanently Connected Swimming Pool and Spa Pumps and to Canadian Standards CAN/CSA C22.2 No. 108-01 Liquid Pumps for Swimming Pools and Spas. (Enclosure 3).
2: Product may have been evaluated to other state and local regulatory standards. Listing status may change. Always confirm status with appropriate agency if in doubt.
3: Flooded suction models do not contain priming/strainer pot.