

Model #PCP025

1/4 HP Auto Pool Cover Pump + GFCI Plug







Inlet	Diameter 13 inches
Discharge	NPSC1-1/4
Pump Cover	PP-GF30
Motor Housing	Q235 chromeplated +ZL104
Pump Body	PP-GF30
Switch Type	PCB
Impeller	PPO-GF30
Seal Design	Framework oil seal
Seal Material	NBR
Oil Filled Motor	No
Power Cord	SJTW 18AWG 10ft
Net Weight	9.5
Gross Weight	12.8
Package Size	12.6*9.6*13.2
Expected Life Cycle	4000 Hours
Motor Wires	Copper or aluminum
Self-Priming	/
Certification	CSA

Features & Benefits:

- Automatically turns on when 2" of water is detected; turns off when water level falls below ¼".
- Fully submersible.
- Corrosion-resistant, reinforced thermoplastic construction.
- Bottom suction design filters debris and removes water down to ½".
- Built-in automatic thermal overload protector.
- 25ft power cord with GFCI protected plug.
- 4 1 year limited warranty.

30.0						
25.0						
20.0						
15.0						
10.0						
5.0						
0.0	500	1,000	1,500	2,000	2,500	3,000
•		,	,		Q(GPH)	-,

Model HP Voltag	Voltago	AMP	Discharge NPT(In)	GPH of water @ Total Ft. of Head				Max.Head Ft		
	Voitage	AIVIF		5 ft	10 ft	15 ft	20 ft	25 ft	Max.Heau Ft	
PCP025	1/4	115	3	1-1/4	2300	1860	1350	680		23